



Rental Grade Unit MLG25 - 20kW Isuzu



TOUGH

- STEEL, LOCKABLE ENCLOSURE
- FULL TUBULAR STEEL FRAME
- DURABLE POWDER COAT FINISH

RELIABLE

- KEY SWITCH ON SINGLE PHASE
- MICROPROCESSOR ON THREE PHASE
- LOW OIL / HIGH TEMP SHUTDOWNS
- START LIMIT MAIN BREAKER
- UP TO 60 HOURS FULL LOAD RUN TIME
- 1 YEAR 1,000 HOUR WARRANTY

EASY TO USE

- SELF-PRIMING ENGINES
- EXTERNAL CONVENIENCE OUTLETS WITH INDIVIDUAL BREAKERS
- EXTERNAL EMERGENCY STOP SWITCH
- THREE PHASE MODELS ALSO HAVE VOLTAGE SELECTOR SWITCH, LUGS AND LUG BOX SAFETY SWITCH, AND AUTOMATIC REMOTE START

Rental Grade Unit

MLG25 - 20kW Isuzu

Output	
3 Phase - Standby (kW/kVa)	20 / 25
Amps (480/208 V)	30 / 69
3 Phase - Prime (kW/kVa)	18 / 23
Amps (480/208 V)	28 / 64
1 Phase - Standby (kW/kVa)	16 / 16
Amps (240 V)	67
1 Phase - Prime (kW/kVa)	15 / 15
Amps	63
AC Voltage - 1 Phase	120, 139, 208, 220, 240, 277
AC Voltage - 3 Phase	208, 220, 440, 480
Frequency Hz.	60
Power Factor	1.0 (1 Phase) / .8 (3 Phase)
Generator (Brand/Type/Insulation)	Marathon / Brushless / H
Sound (dB(A) 23 Feet @ Prime)	66
Size & Weight	
Skid Mounted (L x Wx H)	NA
Dry Weight lb. (kg.)	NA
Operating Weight lb. (kg.)	NA
Trailer Mounted (L x W x H) (in.)	105 x 67 x 56
Dry Weight lb. (kg.)	1570 (710)
Operating Weight lb. (kg.)	2000 (910)
Engine	
Brand	Isuzu
Aspiration	Natural
HP (Prime @ 1800 rpm) (kWm)	31 (23)
Displacement C.I.D. (l.)	134 (2.2)
Cylinders	4
Speed (rpm)	1800
Fuel Consumed (Prime gal. (l.)/h)	2.1 (7.9)
Battery (12 volt)	1 - 12V/720 CCA
Capacities	
Fuel Tank gal.(l.)	56 (212)
Approximate Run Time (hrs.)	26
Coolant qt. (l.)	11.6 (11.0)
Oil qt. (l.)	6.7 (6.3)
AC Distribution	
Main Breaker	90
Voltage Selection	3 Position Switch (Locable)
Voltage Regulation	+/-1%
120V - 20 Amp GFI Duplex	2
240V - 30 Amp Twist Lock	2
240V - 50 Amp Twist Lock	2
Trailer	
Number of Axles & Capacity (lbs.)	1 (3500)
Tire Size (in.)	15
Brakes	None
Hitch	2" Ball / 3" Ring