



<b>TYPE OF ENCLOSURE</b>	<b>V300UC</b>
Canopy	M228



<b>GENSET</b>	<b>Dimensions</b>	<b>Weight</b>	<b>dB(A)@1m</b>	<b>dB(A)@7m</b>	<b>dB(A)@15 m</b>
MV300	4475 m x 1410 mx 2430 m 176 in x 55 in x 95 in	3980 kgs 8775 lbs	79.9	69.9	65.9

**Standard Specifications**

- They protect stationary and mobile generator against the bad weather, against the theft and enables the reduction of the noise level.
- Enclosures are of 12 gauge steel. Steel sheet are electro zinc coated before painting (inside and outside) with a polyester powder rust

inhibiting coat.

- High corrosion resistance: stainless covered with zinc and made in dichromate, bolts and rivets, anodized aluminium alloy hinges flexible seals between body sections.
- Soundfoam between 20 and 50 mm (1 to 2 in) acoustical sound treatment.
- Lifting eye(s) on top of the enclosure fixed to the skid.
- Large doors allow easy access to the generator set for service and monitoring purposes.
- window in "securit" glass mounted on enclosure door for control viewing.
- A critical silencer is mounted inside the enclosure.
- Emergency stop button is accessible from outside enclosure.